

## MV210E Receiver



### **MV210E MicroVision 210E Receiver**

The MV210E is a low cost receiver that provides a 8 character LCD alpha-numeric display and an audible alert to indicate alarms from 900 MHz spread spectrum wireless devices such as Bed Room Stations, Emergency Pull Stations, Smoke Detectors, etc. The MicroVision 210E has a capacity of 32 wireless devices. Each wireless device can be fully supervised.

### **Architects' and Engineers' Specifications**

The Master Station shall be a MicroVision 210E Receiver model number MV210E. It shall operate in the narrow band spread spectrum range with a 902 to 928 MHz operating frequency and 100 KHz bandwidth. It shall utilize redundant, coded signals from Bed Room Stations, Emergency Stations, Staff Assist Stations, Code Blue Stations, smoke detectors, door and window exit transmitters, etc., and display the name of the calling station on its 8 character alpha-numeric display. It shall also have an audible alert and a reset switch.

### **Features**

- Reliable 900 MHz spread frequency transmission
- Capacity of 32 wireless transmitters
- Audible alert
- Reset switch
- Digital display
- Simple operation

### **Specifications**

Dimensions:   Width:       7"  
                  Length:      8.75"  
                  Depth:       1.5"

Power Input: 12VDC (transformer included)